

PRODUCT DESCRIPTION

SAAF PVC & CPVC Cleaner is a clear non-bodied, very fast acting, non-corrosive, caustic free, and highly flammable blend of penetrative solvents, used as dirt and grime remover from PVC, CPVC, ABS and Styrene pipes and fittings.

FEATURES AND BENEFITS

- Easily applied by brush, paper or cloth
- Specially developed for cleaning all types of PVC & CPVC pipes.
- Very fast drying.
- Needs no waiting time
- Can clean all kinds of tools

APPLICATION TOOLS

Dauber Brush or any suitable applicator.

RECOMMENDED USES

- The product is used for cleaning & softening rigid PVC & CPVC pipes, fittings and other materials made up of PVC or CPVC
- Used for cleaning ABS & Styrene pipes and fittings
- Also can be used for removing stains from brushes and cloths

STORAGE

- Should be stored tightly closed and away from direct sunlight in a cool, well-ventilated area between 5°C to 39°C
- Protect from freezing
- Close container tightly when not in use
- Store away from ignition sources, sparks and flames

PACKAGING

Pint = 473 ml (1/2Lit.) Can, Quart = 946 ml (1.0Lit.) Can.

APPLICATION METHOD

1. Shake thoroughly before using.
2. Wear protective clothing like rubber gloves and goggles.
3. The cleaner might attack the PVC surface, therefore avoid prolong contact with the pipe.
4. Apply & store between 5°C to 39°C.
5. Remove all burrs & dirt from the pipe ends.
6. Check the dry fit of the pipe & fitting .The pipe should go easily till $\frac{1}{4}$ to $\frac{3}{4}$ of the way into the fitting snugly.
7. Apply the pipe cleaner with dauber or any suitable applicator inside the fitting & outside the pipe surroundings.
8. Use the appropriate solvent cement for the pipe being joined.

LIMITATIONS

- Do not use it as a thinner for CPVC & PVC Cements.

CLEANING & DISPOSAL

- The Tools & the excess material should be cleaned immediately with this cleaner before it gets dry
- Spillages of the product material should be absorbed into sand, then it is transferred into a suitable container
- Dispose the waste according to the local regulations

SHELF LIFE

24 months shelf life when stored in it's original unopened container between 5°C to 39°C.

HEALTH & SAFETY

The product is inflammable, keep it away from heat, sparks, open flame & other ignition sources, vapors may ignite explosively. Use only in well ventilated areas.

The product should not be swallowed or allowed to come into contact with skin and eyes. Use of suitable protective gloves and goggles is advisable.

If eyes are affected with the adhesive rinse with excess amount of clean fresh water and seek for medical advice .If swallowed seek medical attention immediately and do not induce vomiting help.

HMIS Rating

HEALTH	2
FLAMMABILITY	3
REACTIVITY	0

0 = Minimal; 1 = Slight; 2 = Moderate; 3 = Serious; 4 = Severe; N = No information provided

ADDITIONAL INFORMATION

SAAF IS ALSO MANUFACTURES THE FOLLOWING RANGE OF PRODUCTS

- Solvent Based Adhesives
- Water Based Adhesives
- Flooring Adhesives
- Putties & Sealants
- Coatings
- Concrete Admixtures

For further information, kindly visit our website www.tigind.com